



12918 N. Nebraska Ave.
Tampa, FL 33612
UEI: TK67EL9NPM9
Cage Code: 3VCK4
FEIT: 42-1613127
DUNS: 094261935

POC: Michael Purner
TO: Baldwin County
Baldwin County EOC
23100 McAuliffe Dr
Robertsdale, AL 36567

Sales Quote QU0004873
Date: 10/13/2023

Phone: 251-213-3990
E-Mail mike.purner@baldwincountyal.gov

Certs: SDVOSB, HUBZone SB

Qty.	Manufacturer	Item No.	Description	Unit Price	Total Price
1	Generac	MLTS-3	Mobile Led Tower	\$7,956.50	\$7,956.50
1	Generac	FREIGHT	Freight- Sales	\$1,425.00	\$1,425.00
1	Generac	MLTS-4	Mobile Light Tower	\$8,410.50	\$8,410.50
1	Generac	FREIGHT	Freight- Sales	\$1,425.00	\$1,425.00
1	Generac	MLT6SMDS-STD3	6kW Vertical Mast LED Light Tower, Manual Winch, Small Body Series	\$9,265.50	\$9,265.50
1	Generac	FREIGHT	Freight- Sales	\$1,425.00	\$1,425.00

FOB: Destination
Delivery Time: 70 Days ARO

Quantity 1 - MLTS-3: Diesel 1.4kW LED Light Tower, brushless, capacitor regulated, Mitsubishi engine, manual winch
Estimated Delivery: 8-10 weeks ARO, subject to change.

Quantity 1 - MLTS-4: Diesel 2.4kW LED Light Tower, brushless, capacitor regulated, Mitsubishi engine, manual winch, 2.4kW export power.
Estimated Delivery: 4-6 weeks ARO, subject to change.

Quantity 1 - MLT6SMDS-STD3: Diesel 6kW LED Light Tower, (4) 320W G4 LED's, brushless excitation, capacitor regulated, Mitsubishi engine, vertical mast, manual winch, 5kW export power.

Sourcwell Member ID 87730
Generac Sourcwell Contract 020923-GNR

*** Please see attachments for machine data and warranty information. ***
*** Shipping to Robertsdale, AL included. ***
*** Unit arrives on flatbed trailer. ***
*** Forklift/crane needed to offload. ***
*** Offloading is customer responsibility ***

Subtotal: \$29,907.50
Tax: \$0.00
Total: \$29,907.50

Jay Johnson,
O. (813)631-0000
F. (813)631-0008
jay@federalcontractscorp.com



12918 N. Nebraska Ave.
Tampa, FL 33612
UEI: TK67EL9NPMD9
Cage Code: 3VCK4
FEIT: 42-1613127
DUNS: 094261935

POC: Michael Purner
TO: Baldwin County
Baldwin County EOC
23100 McAuliffe Dr
Robertsdale, AL 36567

Sales Quote QU0004873
Date: 10/13/2023

Phone: 251-213-3990
E-Mail mike.purner@baldwincountyal.gov

Certs: SDVOSB, HUBZone SB

Terms and Conditions:

- Quote valid for 30 days
- Terms: Net 30
- Unless otherwise specified, full dock or off-loading capabilities required to avoid additional charges.
- If using a purchase card, a credit card surcharge may apply.
- Certificate of Origin/MSO will not be released until payment in full has been received.

Jay Johnson,
O. (813)631-0000
F. (813)631-0008
jay@federalcontractscorp.com

SPECIFICATIONS

ENGINE SYSTEM

- Mitsubishi® L3E
- Diesel fueled
- EPA Tier 4 Final
- 3 cylinder
- 0.95 L displacement
- Power @ 1,800 rpm – HP (kW):
 - Prime: 11.3 (8.4)
 - Standby: 12.2 (9.1)
- Air filter: Dry type cartridge

Fuel System

- Polyethylene tank – 39.9 gal (151.04 L) capacity
- Run time – hr:
 - Lights only: 164*
 - 100% load: 67*
- Fuel consumption – gph (Lph):
 - Lights only: 0.2 (0.9)*
 - 100% load: 0.6 (2.3)*
- Fill port diameter: 3.5 in (89 mm)

Cooling System

- Liquid cooled

Lubrication System

- Oil filter: Full flow, spin-on type
- 1,000-hr service interval**

**Data based on engine manufacturer and field test data after 100-hr engine break-in period. Actual results may vary, according to factors such as age and maintenance of equipment, environmental conditions, and fuel density. For fuel and maintenance recommendations, see owner's manual.*

***For maximum service interval, replace oil filter after 50-hr break-in period. For oil filter model number, see owner's manual.*

GENERATOR

- 60 Hz engine/generator
- Marathon Electric® brushless
- Up to 6 kW output
- 120/240 VAC, 20/30 A
- $\pm 6\%$ capacitor voltage regulation

CONTROLS

- Illuminated control panel with sealed switches
- Key-activated switch with 4 positions (OFF, RUN, GLOW PLUG, START)
- One switch controls all light fixtures
- Digital hour meter
- Automatic shutdown for low oil pressure and high coolant temperature







Picture shown may not reflect actual configuration.

FLOODLIGHTS

- Four 320 W LED fixtures
- Aluminum and polymer housing
- Efficiency: 147 lpw
- Lm/fixture: 47,000
- Total lm: 188,200
- Coverage at 0.5 ft-c: 25,068 ft² (2,329 m²)
- IP65 rated fixtures
- Fixture-mounted drivers

Illumination Data



ELECTRICAL SYSTEM

- 30 A start trip breaker (ensures no-load condition exists at start-up)
- Floodlight circuits with sealed 10 A breakers
- Convenience receptacles with individual breakers:
 - One 120 VAC, 20 A, GFCI, duplex outlet (NEMA 5-20R type)
 - One 240 VAC, 30 A, twistlock outlet (NEMA L14-30R type)
- Wiring is sized and fused to required amperage draw
- 440 CCA wet cell battery

MAST

- Vertical operation and storage
- Five tubular steel sections with polymer guides
- Ground-adjustable light fixtures
- Winch: Dual handle, manual crank
- Distinctive angled fixture mount for common light distribution
- Rotation: 359° range of motion, adjustable from ground during full extension
- Industrial black powder-coat finish
- Self-retracting, coiled mast cord, winch cover

ENCLOSURE

- Hood:
 - Injection-molded with UV protected colorant
 - Flip-up design for ease of service
- Sound rating: 63 dB(A) at 23 ft (7 m) @ prime power
- Lifting point and fork pockets
- Multi-lingual operating and safety decals
- Illuminated license plate holder
- Document holder with owner's manual – includes AC and DC wiring diagrams


TRAILER

- Tubular steel frame
- 2 in (50.8 mm) ball hitch
- Three 1,200 lb (544 kg) leveling jacks – lockable into stowed positions
- Folding tongue
- Side outriggers
- 7,800 lb (3,538 kg) safety chains with spring loaded safety hooks
- Transportation tie-downs
- DOT approved LED lights: Tail, side, brake, and directionals
- 2,200 lb (998 kg) leaf spring axle
- Tires: ST175/80, 13 in. rim

OPTIONS

- | | | |
|-------------------------|-------------------------------|-----------------------|
| • Electric winch | • Battery charger | • Engine block heater |
| • Positive air shutdown | • Battery disconnect | • Fuel filter heater |
| • Tandem tow | • Power Zone® Plus controller | |

DIMENSIONS



A	B	C	D	E
118 in (3 m)	101 in (2.6 m)	23 ft (7 m)	57 in (1.45 m)	10 ft (3.05 m)

WEIGHT

- Dry: 1,310 lb (594 kg)
- Operating: 1,600 lb (726 kg)

AMBIENT CLIMATE RATINGS

- Maximum wind speed: 65 mph (105 km/h)
- Maximum air temperature – °F (°C):
 - Lights only: 120 (49)
 - 100% load: 104 (40)

WARRANTY

- Tower: 1 year, unlimited hours/2 years, 2,000 hours
- LED modules and drivers: 5 year limited warranty

CERTIFICATIONS

CSA approved, listed

FOR MORE INFORMATION

Owner's manual is available at www.generacmobileproducts.com/service-support/manuals.