



Service Bypass Panel Model	Rated Input Voltage	Rated Output Voltage	Rated Input Current (Arms)	Max Output Current (Arms)	Max Output Power (Watts / VA)
SBP3000	100-120V 50/60Hz, 1P+N+PE	100-120V 50/60Hz, 1P+N+PE	30	30	7200
	220-240V 50/60Hz, 1P+N+PE	220-240V 50/60Hz, 1P+N+PE			
	200-240V 50/60Hz, 2P+PE	200-240V 50/60Hz, 2P+PE			
SBP16KP	200-240V 50/60Hz, 1P+N+PE	200-240V 50/60Hz, 1P+N+PE	100	100	24000
	230/400V 50/60Hz, 3P+N+PE	230V 50/60Hz, 1P+N+PE			
	200-240V 50/60Hz, 2P+PE	200-240V 50/60Hz, 2P+PE			
	100/200V, 120/208V, 120/240V 50/60Hz, 2P+N+PE	100/200V, 120/208V, 120/240V 50/60Hz, 2P+N+PE			

The above table represents the electrical ratings of the Service Bypass Panel and not those of the UPS. Service Bypass Panel ratings must be equal to or greater than those of the UPS to which it is connected. System load must not exceed electrical rating of UPS. e.g. if a 7200VA SBP is used with a 3000VA UPS the maximum load that the system will support is 3000VA.

885-1956B_REV03 SZ









