

BID #WG19-22 SPECIFICATIONS

Baldwin County desires bids for the provision of uniforms for the Sheriff's Office and Corrections Center. **This bid will be for uniforms and uniform accessories ordered during a one-year period beginning the day of Bid Award.**

It is the intent of the Commission to award to the lowest bidder that meets the specifications for each item. The **Propper Ripstop Pants & Shirts** as well as **Armorskin Ripstop Pants & Shirts** will be awarded to **one bidder** (lowest responsible bid) in order for the garments to have matching dye lots.

No alteration cost should be included for garments. Alterations will be done by Baldwin County.

DELIVERY

Delivery shall be as soon as possible, but not more than thirty (30) business days after receipt of order. Orders will be delivered as specified on the Purchase Order. All items shall be bid as listed in specifications. No substitutes will be accepted. If an item is discontinued the successful bidder must notify the Purchasing Officer and submit a sample of the substituted item for evaluate before the substituted item will be allowed to replace the original bid item.

CONTRACT PERIOD

It is the intent of the Baldwin County Commission to award this contract for a twelve (12) calendar month period. However, the Baldwin County Commission may, at their option and in agreement with the Successful Bidder, renew the contract for up to two (2) additional years (2020 and 2021), in twelve (12) month increments. The Baldwin County Commission will, in writing, notify the Contractor thirty (30) days prior to expiration of the 2019 contract with its intent to extend the contract. The prices for 2019 shall also apply to the extension period(s).

PRICING

The price shall include all charges, including but not limited to delivery and destination charges. Any item being returned that was ordered but was shipped incorrectly by the supplier, return shipping charges will be prepaid by the supplier. If an item is returned that was received per the order, return shipping charges will be paid by Baldwin County.

CLOTHING SAMPLES

Samples may be requested in order to evaluate the lowest responsible bidder. Samples provided will be returned after the award. Samples will be shipped to Mrs. Wanda Gautney, 257 Hand Avenue, Bay Minette, AL 36507. **Vendors must provide a Return Shipping Label for the return of their samples.**

ACCESSORIES

The bidder will be allowed to bid additional items that are consider accessories that are not listed in the specifications.

BID RESPONSE FORM AND OTHER REQUIRED DOCUMENTATION

Supplier will use the Bid Response Form that has been included with this document for their bid. Attached to the Bid Response Form will be the marked brochures and detailed listing.

The bidder shall provide a listing of the items being bid. The listing shall consist of Product Number, Brand Name and Description, Unit Price. The bidder is allowed to offer additional items, that would be known as accessories or footwear that are not listed in the specifications.

Brochures will be provided that show garment and accessories style, including footwear. Each item will be identified with a garment number or style number clearly marked on the brochures. THIS MUST ACCOMPANY THE BID RESPONSE FORM. IF THIS IS NOT INCLUDED WITH THE RESPONSE FORM THEN THE BID WILL NOT BE ACCEPTED.

Supplier will make delivery of ordered items within 30 days of receipt of the Purchase Order.

UNIFORM SPECIFICATIONS

Item: 1. Convertible Jacket

Shell Fabric:

Brookwood Technique. 100% Tectel Nylon. 3-3.5oz. sq. yard. Poplin Weave. Everdry finish for storm proof protection.

Permanent Lining:

104 x 86 Thread count. 100% nylon Taffeta.

Zip Out Lining:

Face - 100% Nylon Taffeta

Batt - Quilted 200-gram body with 150 gram sleeves thinsulate by 3M

Back - 100% Nylon Taffeta

Design:

The jacket shall be a cull cut, waist length model with zip-in/zip-out liner, zipper front and shirred waistband. Coat construction shall be used throughout with body and sleeves being fully lined.

Design:

The jacket shall be a cull cut, waist length model with zip-in/zip-out liner, zipper front and shirred waistband. Coat construction shall be used throughout with body and sleeves being fully lined.

Body Detail:

The front shall be plain with patch pockets, flaps and badge tab. For shape retention, the front shall be interlined with heavy weight Pellon. The inside facings shall be made of outer fabric and are to be sewn on top of the nylon lining which extends to the front edge of the jacket. There shall be a one piece back. There is to be a separate 2 ½" waistband shirred with 2" heavy duty elastic. The entire waistband is to be shirred with the exception of an area 5 ½" on either side of the front opening. The shoulders shall have pads. A self-goods reinforcement strip shall be sewn on the inside of the jacket joined at the top of the waistband and extending from side to side. It shall also contain a tunnel for flexcuff.

Inside Detail:

On the left side of the coat, there shall be a gun pocket installed in the permanent lining of the coat to accept a small frame hand gun. The gun pocket shall have a minimum opening of 4 ½" and be a minimum of 6" deep. The gun pocket shall be furnished with a strap and a snap closing. Bartacks shall reinforce the opening. There shall be two cut-in pockets on the left and right sides measuring approximately 5 ½" wide and 6" deep.

Zip-Out Liner:

Shall be full body and sleeves with inside right pocket and shall be constructed to allow entry to gun pocket.

Sleeves:

The sleeves shall be coat style set in with a single needle machine. The bottom of the sleeve shall have a gusset opening and close with a storm cuff with Velcro closure for adjustable fit. The cuff shall be interlined with Pellon. There shall be an elastic sleeve loop for liner stability on the inside of the cuff.

Pockets:

There shall be two patch pockets with box pleats, finishing approximately 6 ¼" wide and 7 ½" deep. Flaps shall be scalloped and self-lined. They shall close with snaps or Velcro on the points and with a centered buttonhole. The pockets shall be interlined with Poly/Cotton twill in such a way as to create hand-warmer pockets with an opening of approximately 5 ½" on the side. The left patch packet is to have a pencil opening at the top of the flap. Both the pockets and the flaps are to be bartacked.

Collar:

The collar shall be made using self-material. It shall be interlined with Pellon.

Epaulets:

The epaulets shall be made of self-goods. They shall be sewn into the sleeve head seam, "X" stitched and tacked to the jacket at the neck.

Badge Tab:

The badge tab shall be made of the outer fabric, 1" wide and 2 metal eyelet's spaced vertically apart. It shall be centered 2 ½" above the left pocket flap.

Zipper:

There shall be an YKK #5 molded nylon zipper.

Buttons and Snaps:

The pockets flaps and epaulet shall be secured with 24 ligne metal toggle buttons, flaps and epaulets shall close with 24 ligne metal buttons.

Thread:

All sewing is to be done with Polyester core thread or 100% Spun Polyester thread.

Size Tag and Care Instructions:

Each jacket shall have a sewn in label giving care instructions and shall be marked with lot number, size, fiber content and WPL number.

Finishing and Pressing:

All loose threads shall be removed. Each jacket shall be pressed and shaped properly.

Warranty:

One year against workmanship or fabric defects.

Color:

Brown

Item 2. Rain Coat - (samples for Rain Coat MUST be supplied with your Bid Response)

Material: (NO SUBSTITUTES ALLOWED)

Style: 48125

100% Nylon Oxford reverses to HI-VIS

5.11 High Visibility Reversible Rain Coat, meets the requirements of ANSI/SEA 07-2010, Waterproof, adjustable, reversible. Pass-through pockets, Mic loops at the shoulders, integrated badge tab.

Item 3. Long Sleeve Flying Cross Shirt 100% Visa ® System 3 Polyester Command Mens

Fabric:

Flying Cross, Style FC-33W7800Z, 100% Polyester, Plain Weave. Weight 7-7 1/2 ounces per linear yard.

Creasing:

There shall be five stitched-in sharp military creases on all shirts. One crease on each front to be centered vertically. Front Creases shall not be through pockets and flaps. Spacing for three military creases across shirt back to be proportionate to the size of the shirt.

Front:

The left front shall have a top center placket 1-1/2" wide with two rows of stitches 7/8" apart. The shirt will have 7 buttons and buttonholes on the front; spacing between each will be 3-3/4". Top center placket to have woven interlining of 250 Dacron. Non-woven interlining unacceptable and shall be cause for rejection. The fronts shall be joined to the yoke so that both raw edges of the yoke are turned under, with the front sandwiched between, and then all three are stitched down with a 1/16" raised stitch. Safety stitch joining unacceptable. A 15" nylon zipper, to be set below the second button and buttonhole, shall accomplish front closure. The top, second and bottom buttons to be attached to the right front, the balance to be sewn over the buttonholes on the left front.

Collar:

Collar points to measure 3 1/8" long with ultrasonically fused-in Mylar stays, Collar to have woven interlining of #250 Dacron. Stays to be 3" long, 3/8" minimum width and to be fused to the underside of collar interlining. Stays applied directly to collar material itself unacceptable. Collar height at rear 1-1/2". Collar topstitched 1/4" off the edge. Collar stand to measure 1-5/16" at rear and band to be interlined with "Crease-N-Tack." Collar material itself (top or underside) shall have no fusing to Mylar stays or collar interlining.

Shoulder Straps:

Shoulder Straps to be two-piece pointed, 1/4" topstitched and to be set on yoke with leading topstitch conforming with front joining seam. To measure 2" at sleeve tapering to 1-3/8" and set not more than 1/2" from collar set seam. Cross-stitched approximately 2" from sleeve seam. Shoulder strap to have functional buttonhole to attach to sewn button on shoulder of shirt. Edge stitched shoulder strap construction unacceptable.

Badge Reinforcement:

Two-ply sling 1" wide centered over left pocket and stitched to shoulder seam and flap setting stitch. It shall have two (2) buttonhole eyelet's 1-1/4" from top of pockets flap spaced 1-1/4" apart and centered on sling.

Pockets:

Two breast patch pockets with mitered corners and 1-1/2" stitched pleats. Pleats shall be stitched top and bottom and full length of pleat to prevent spreading. Pocket to measure 5-5/8" wide, 6" deep. Left breast pocket to have one (1), 1/2" pencil stitch. Each pocket to have hook Velcro 3/4" long by 1/2" wide, positioned on both edges of pocket to correspond with outer scalloped flap points as specified. Velcro to be stitched all sides and to be sewn through pocket and shirt for added reinforcement.

Flaps:

Two piece deep scalloped design to measure 5-7/8" across and 2-3/4" in depth at center point, 2-1/4" at sides. Secured to shirtfront approximately 3/8" above pocket. Left flap to have invisible pencil opening 1-1/2" to correspond precisely with pencil slot of pocket. (Stop & start stitching for pencil opening unacceptable and shall be cause for rejection.) Flaps to be 1/4" topstitched. Flaps to have woven interlining of #250 Dacron. Creased and edge stitched pocket flap to have looped Velcro 3/4" long by 1/2" wide stitched all sides, positioned on outer points of both pocket flaps to secure with corresponding Velcro strips on shirt pocket. Each flap shall have a button centered on uncut sewn buttonhole.

Sleeves:

Sleeve vent shall have round one-piece elbow reinforcement and vent facing. Lower facing shall measure approximately 1/2" wide.

Cuffs:

Two piece 1/2-inch hemmed cuff with 1/4" topstitching. Cuffs to measure 3" in depth with rounded corners (barrel cuffs). Cuffs to have two buttons and corresponding buttonholes set vertically with one button and buttonhole in center of facing. Cuffs to have woven interlining of #250 Dacron.

Buttons:

First grade 20-ligne melamine.

Sewing:

Collar, shoulder straps, pocket flaps and cuffs to be topstitched 1/4" off the edge. Sleeve inserting and side close felling seams are to be safety stitched.

Thread:

All sewing threads to be color fast polyester wrap to match.

Interlinings:

Collar, cuffs, pocket flaps and top center to be interlined with #250 Dacron. Collar band interlining to be "Crease-N-Tack".

Construction:

Collars, flaps and cuffs are made with conventional construction. Top ply, bottom ply and interlining are first stitched together, then turned right side out and finally topstitched.

Stamping and Care Instructions:

Neck size and sleeve length to be stamped in collar band with style and cut number. A permanent size tab is to be sewn in with label to the inside yoke. Care instructions to be attached to the tail of the shirt.

Packing:

Shirts to be polybagged individually.

Warranty:

One year against workmanship or fabric defects.

Item 4: Sheriff Logo Safety Vest (w/Optional Body Worn)

Oralite Style # 343R-S Zip-Front Safety vest; Color: Hi-Vis Yellow

FABRIC:

3.7 oz. per square yard, 100% Spin-dye woven Polyester

Color: fluorescent yellow

TRIM:

- Binding: 100% polyester (self-fabric) (Color: fluorescent yellow)
- Hook and loop: woven nylon base. (Color: fluorescent yellow)
- Eyelets: aluminum, black enamel finish
- Ribbon: 100% nylon Taslan. (Color: black)
- Reflective trim: 1-1/4" Reflexite crosswalk trim
2-1/2" Reflexite crosswalk trim for front panels
- Zipper: 11-1/2" single pull, breakaway (non-locking) separating zipper. Size #5 coil.

FRONT:

Vest has a zipper front closure measuring 11-1/2" long. There shall be a pencil pocket made of shell fabric, measuring 2-1/8" by 5-1/4" and allow for two pens. The pocket should fit above the top horizontal Reflexite trim and above the inner vertical Reflexite trim on the wearer's left side. There shall be hook & loop closure at shoulder for breakaway option.

BACK:

One piece back with Reflexite trim detail with hook & loop closure at shoulder for breakaway option.

SIDE ADJUSTMENTS:

There shall be 2 side tabs on each side with hook and loop attachment for closure and adjustments. Side tabs shall measure 4-1/2" high by 9-1/2" long. The front shall have two rows of 1" loop attached above of the edge of the 2-1/2" horizontal Reflexite trim. The side tabs shall have 1" X 3" horizontal hook. An additional piece of 1" x 1" hook with loop shall be sewn on 1-1/2" away from the edge of the first stripe of hook.

REFLECTIVE TRIM PATTERN:

There shall be Reflexite reflective trim vertically down the front and back chest and across the back aligning with the side tabs. The side tabs will have Reflexite reflective trim to align with bottom stripes. There shall be one (1) stripe of 2" Reflexite reflective trim running horizontally across the front. There shall be four (4) stripes of 2-1/2" Reflexite reflective trim running vertically down the back aligning at the

shoulder and ending at the top horizontal stripe. The Reflexite trim shall run in pairs with 2" spacing between them.

SHOULDER CLOSURE:

There shall be a hook and loop attached on shoulder for breakaway feature. The shoulder shall have 5-5/8" x 5/8" loop on the front shoulder to fasten to a 5-5/8" x 5/8" on the back shoulder. (For size M)

BINDING:

The vest shall be bound with high-visibility self-binding on neck, sides, and hem.

MICROPHONE TABS:

There shall be a microphone tab sewn to both the left and right front approximately 4-1/4" from the shoulder seam, consisting of two plies of shell fabric. They shall measure 2" x 1".

CUSTOMIZATION:

- **BODY CAMERA ATTACHMENT:**

Customized zipper access to holster and phone/camera uses YKK brand #3 reverse tape coil zipper in 9" length. Armorskin access is from front right side of placket and shirt access from under placket, both to attachment location on wearers left side for men & women. Placement of camera holster and patch is specific for optimal performance of equipment and stability of application. Main eye-hole is created by using a Stimpston non-rusting metal #5.5 @ 11/16" rolled rim grommet and washer. Velcro USA hook and loop patch with two width measurements; one for in-production addition or second for post-production customization add-in; ref: COM-BW-1022 & COM-BW-1023. Patch uses Tandy size# 16 Ligne non-rusting snaps with specific spacing to accommodate lightweight polymer holster facilitating removal and insertion for user.

THREAD:

All thread shall be polyester wrapped on monofilament polyester. Color to match.

STITCHING:

All stitching conforms to Federal Standard 751 specifications (FED-STD-751). All stitch types are sewn at stitch per inch (S.P.I.) rates individually set by operation at no less than 10 S.P.I. and not more than 12 S.P.I. to insure extended sewn wear life. All thread tension is evenly maintained to eliminate right or loose stitching. All seam allowances are to be maintained so that there are no raw edges, run offs, twist, pleats, puckers or open seams.

SIZES:

Permanent size marking to be located inside center back neck seam.

ANSI LABELS:

ANSI labels shall be placed on the left and right-side tabs.

PRESSING & FINISHING:

Vest shall be carefully pressed by hand in a first-class manner. All loose threads to be thoroughly trimmed.

STANDARD SIZE RANGE:

Unisex: M (S-M), XL (L-XL), 3XL (2XL-3XL), 5XL (4XL-5XL)

MEASUREMENTS:

Unisex: Size M, Regular:

Across Chest:	16.25	(plus or minus 0.5 inches)
Across back:	17	(plus or minus 0.5 inches)
Center Back Length:	19.5	(plus or minus 0.5 inches)

Item 5. MEN'S TROUSERS**Fabric:**

Style: Flying Cross/Fechheimer Item #42283: 75% Polyester/25% Wool. 11 ½ to 12 oz. Per linear yard. Serge. No more than 25% wool will be accepted in trousers.

Style:

Trouser styling shall be T-1: plain front, two (2) quarter top front pockets, and two (2) hip pockets professionally finished with no visible topstitching. Work wear industrial style construction is unacceptable and shall be cause for rejection.

Lining Material:

The pocketing and fly lining material shall be 70% Polyester / 30% Cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 48 count. Pocketing must have a durable press finish and the color of the pocketing must be black.

Waistband:

The trouser will be made with the Freedom Fit waistband system, which is designed to provide the wearer with a more comfortable and better fitting trouser. The waistband shall be constructed using the "closed method" and shall measure a minimum of 1-7/8" wide when finished. The waistband closure shall be accomplished with a single crush proof hook and eye centered on the waistband for maximum wearer comfort. The hook and eye shall be reinforced with 7/8-inch non-woven stay tape that is anchored with topstitching through and through to the top of the waistband (bartacks in place of topstitching shall be cause for rejection). In addition to the stitching of the waistband when it is set onto the trouser, the waistband must also be topstitched below the waistband seam through the waistband curtain for added strength. The back-center seam of the trouser to be finished to allow for alterations (with ample basic trouser fabric and waistband curtain material to allow trouser size to be increased at least one size). The outlet in the seat is to be in proportion to waist outlet so seat may also be let out. Seat seam must be sewn with a tandem needle machine (double-needle stitch) for maximum strength. The waistband curtain is composed of two elastic components, which give it two-zone comfort fit and breathability.

The top part of the waistband curtain is interlined with a 1-1/2" elastic band that has two functions. It stabilizes the waistband, preventing waistband rollover, and allows for a comfort stretch when the wearer bends or sits. This elastic is around the entire waistband and is constructed with and around the entire waistband and is constructed with an open weave to allow for breathability. The specifications for the upper elastic are as follows:

Width: 1 1/2"
Overall content: 38% Polyester, 45% Nylon, 17% Spandex
Stretch: 20%

The upper part of the waistband curtain interlining (elastic band) is to be lined the same color as the pocketing material and it shall be cut on a 45-degree bias to allow for maximum stretch. The waistband basic trouser fabric shall be cut across the cloth to allow for maximum stretch in synergy with the Freedom Fit Waistband. The lower part of the waistband shall also be the same color as the pocketing material and is designed to stretch over the hips for comfort and helps keep the trouser positioned properly on the waist. This elastic is also woven with an open weave for maximum breathability. The lower elastic portion of the band has an area of exposed Neoprene rubber, which acts as a shirt keeper. The specifications for the lower elastic are as follows:

Width: 1 3/4"
Overall Content: 13% Polyester, 49% Nylon, 16% Spandex, 22% Rubber
Stretch: 55%

The three (3) rubberized strands match the waistband curtain color and are designed to keep shirts tucked in for neat appearance (use of silicone strip or strips instead of rubberized strands shall be cause for rejection).

Belt Loops:

There shall be a minimum of seven belt loops 3/4" in width of double thickness. Each loop must have a non-woven interlining for added durability. All loops (except back center) must be sewn into the top and bottom of the waistband ("dropped" belt loops that are tacked to the outside of the trouser all around waist shall be cause for rejection). The top of the belt loops (except back center) shall be sewn into the waistband curtain seam with a Rocap machine using a zigzag stitch. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband to allow for easier waist alteration.

Fly:

Trouser shall have a brass metal zipper with memory lock brass slider secured by metal stopper at base. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic trouser fabric (tabs made of pocketing materials or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same material and color as the pocketing. The fly lining shall be sewn to the left fly continuing below the zipper into the crotch area in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. Topstitching of fly to be installed with automatic "J" stitch equipment eliminating puckering and providing a clean finish. There shall be firm straight bartack at the bottom of the fly going through the zipper tape for maximum strength. Bartack shall line up with starting point of "J" stitch.

Seat:

Seat must be sewn with a Tandem Needle Machine (double-needle stitch) for maximum durability.

Pockets:

The two (2) front pockets will be quarter top style with a minimum opening of 6" and a minimum depth of 5-3/4" measured from the bottom of the opening. Front pockets to have firm straight bartacks at top and bottom of pocket openings. Pockets shall be constructed using the stitch, turn, and topstitch method. Front pocket facing, and barrier to be made of the basic trouser fabric. Facing shall be a minimum of 1" and barrier shall measure a minimum of 2" (measured to the inside edge of pocket lining).

The two (2) hip pockets shall have a minimum 5-3/8" wide (bartack to bartack) opening and a minimum depth of 5-3/4" measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on an automatic welt machine. The welts shall be finished in such a manner that there is no topstitching (topstitched hip pockets shall be cause for rejection). The corners of the hip pocket openings shall have straight bartacks for reinforcement (use of triangular bartacks shall be cause for rejection). Hip pocket facing and barrier to be made of basic trouser fabric. Facing shall be a minimum of 3/4" and barrier shall be a minimum of 1-1/2". The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the top to form an opening for a button. A button shall be located below the bottom welt corresponding in location with the tab, which shall be interlined with non-woven for added durability. There shall be a dart centered above each hip pocket to waistband. Dart shall be approximately 2-3/4" long tapered from 3/8" at waistband and shall be installed with automatic equipment for a clean non-puckered finish.

The watch pocket shall be located on the right front at the waistband. This pocket shall have a minimum opening of 2-5/8" and a minimum depth of 2-7/8". The front of the pocket shall be made of pocketing fabric and the back of the pocket shall be made of basic fabric and the two pieces are securely stitched together. Each corner of the pocket opening shall have firm straight bartacks.

Creases:

The leg creases, front and back will have a silicone bead put in by using the Lintrak process.

Stripe:

Trousers shall have a 3/4" stripe of the 100% polyester material in brown (7451-7062) Milekin.

Stripe is to be sewn from the bottom of the waistband to the bottom of the trouser leg and is to be sewn into the trouser side seam.

Labels:

Trouser must have a permanent label providing care instructions and small woven label indicating waist size. A removable paper ticket showing the size, fabric content, cut number, and WPL or RN number must be on the outside of the waistband. Ticket to be matchbook style installed with plastic staples for easy removal without damaging trouser material and showing size when trousers are stacked.

Origin:

Make in USA

Warranty:

One year against workmanship or fabric defects.

Color:

1. **Taupe** with **3/4" brown stripe** sewn on seam from waistband to bottom. (Brown 3/4" Stripe to be sewn into seam of pants - not sewn on top of seam)

(A) Supervisors - **1/2" gold** (not yellow) stripe sewn on top of the 3/4" brown.

Sample of stripes will be supplied with Bid Response.

2. **Brown**

Item 6. WOMEN'S TROUSERS

Fabric:

Style: Flying Cross/Fechheimer Item #47293: 75% Polyester/25% Wool. 11 1/2 to 12 oz. Per linear yard Serge.

Style:

Garment shall be manufactured from an up-to-date women's pattern for comfort and easier sizing. The trouser styling shall be T-1: plain front, two (2) quarter top front pockets, and two (2) hip pockets professionally finished with no visible topstitching. Work wear industrial style construction is unacceptable and shall be cause for rejection.

Lining Material:

The pocketing and fly lining material shall be 70% Polyester / 30% Cotton, 2.9 oz. per square yard (60" width) with a minimum 78 x 48 count. Pocketing must have a durable press finish and the color of the pocketing must be black.

Waistband:

The trouser will be made with the Freedom Flex waistband system, which is designed to provide the wearer with a waist expansion of 1 1/2" to 3". The waistband shall measure a minimum of 1-7/8" wide when finished. The flexible expansion split portion of the waistband shall be to the front of the trouser side seam and there shall be a 1/4-inch wide side belt loop positioned to hide the expansion split of the waistband. The waistband curtain shall consist of two different styles for maximum waistband expansion to enhance wearer comfort, fit and appearance. The front of the trouser (to the expansion split) waistband curtain style shall consist of a 2-inch wide elastic section that incorporates Tru-Grip, a 1/2" "surface area composed of thin 55-gauge rubber for maximum comfort and performance. The Tru-Grip acts to help keep shirts tucked in securely. (Use of a single silicone strip or strips instead of 1/2" wide rubberized surface area shall be cause for rejection.) The back half of the trouser waistband curtain shall finish a minimum 1-1/8" wide and is to be made of black pocketing material and shall be attached to the top of the trouser with a zigzag stitch. The waistband curtain must also contain Tru-Grip and will line up with the Tru-Grip on the front of the expansion split. (Substitution of a single silicone strip or strips in place of Tru-Grip shall not be acceptable and shall be cause for rejection.)

The waistband curtain is composed of a wet laid non-woven canvas weighing 3.3 oz. per square yard. The canvas is covered in the same color and material as the pocketing. The 1/2" rubberized surface area is positioned 1-1/4" up from the bottom of the curtain. The specifications for the rubberized Tru-Grip curtain are as follows:

Width: 1-1/8 inch
Warp & Filling: 300 Denier Texturized Polyester
Rubber: 55 Gauge
Count: 32-36 yarns per inch
Content 59% Polyester 41% Rubber

To complete the Freedom-Flex Waistband System, there shall be a 1-1/4" wide elastic component sewn into the back half of the waistband curtain to allow for the stretch and recover of the waistband to comfortably fit the wearer's waist size. There shall be a bartack for strength and durability sewn at the stress point on the waistbands where it joins the front elasticized waistband curtain joining stitching (positioned, on the waistband above the front pocket.) The waistband closure shall be accomplished with one crush proof hook and eye centered on the waistband for the wearer comfort. The hook and eye shall be reinforced with a 7/8" non-woven tape that is anchored with topstitching through and through to the top of the waistband (bartacks in place of topstitching shall be cause for rejection.) In addition to the stitching of the waistband when it is set onto the trouser, the waistband must also be topstitched below the waistband seam of the trouser to be finished to allow for alterations (with ample fabric and curtain material to allow trouser size to be increased at least one size). The outlet in the seat is to be proportional to the waist outlet so the seat may also be let out. Seat seam must be sewn with a tandem needle machine (double-needle stitch) for maximum stretch.

Belt Loops:

There shall be a minimum of seven belt loops 3/4" in width of double thickness. Each loop must have a non-woven interlining for added durability. All loops (except back center) must be sewn into the top and bottom of the waistband ("dropped" belt loops that are tacked to the outside of the trouser all around waist shall be cause for rejection). The top of the belt loops (except back center) shall be sewn into the waistband curtain seam with a Rocap machine using a zigzag stitch. The bottom of the center back loop shall be tacked to the trouser and the top of the loop tacked to the outside of the waistband to allow for easier waist alteration.

Fly:

Trouser shall have a brass metal zipper with memory lock brass slider secured by metal stopper at base. There shall be a French Fly tab closure on the inside of the right fly. The tab shall be double ply made of the basic trouser fabric (tabs made of pocketing materials or a "grown on" French Fly will be cause for rejection). The right fly shall be lined with the same material and color as the pocketing. The fly lining shall be sewn to the left fly continuing below the zipper into the crotch area in a neat and durable manner. A button shall be located on the left fly corresponding with the French Fly tab to provide a clean and comfortable closure. Topstitching of fly to be installed with automatic "J" stitch equipment eliminating puckering and providing a clean finish. There shall be firm straight bartack at the bottom of the fly going through the zipper tape for maximum strength. Bartack shall line up with starting point of "J" stitch.

Seat:

Seat must be sewn with a Tandem Needle Machine (double-needle stitch) for maximum durability.

Pockets:

The two (2) front pockets will be quarter top style with a minimum opening of 6" and a minimum depth of 4-1/2" measured from the bottom of the opening. Front pockets to have firm straight bartacks at top and bottom of pocket openings. Pockets shall be constructed using the stitch, turn, and topstitch method. Front pocket facing, and barrier to be made of the basic trouser fabric. Facing shall be a minimum of 1" and barrier shall measure a minimum of 2" (measured to the inside edge of pocket lining).

The two (2) hip pockets shall have a minimum 5-3/8" wide (bartack to bartack) opening and a minimum depth of 5-3/4" measured from the bottom of the pocket opening. Hip pockets shall be constructed using the double welt method on an automatic welt machine. The welts shall be finished in such a manner that there is no topstitching (topstitched hip pockets shall be cause for rejection). The corners of the hip pocket openings shall have straight bartacks for reinforcement (use of triangular bartacks shall be cause for rejection). Hip pocket facing and barrier to be made of basic trouser fabric. Facing shall be a minimum of 3/4" and barrier shall be a minimum of 1-1/2". The left hip pocket shall have a centered tab made of basic cloth inserted into the top welt with bartacks at the top and bottom of the top to form an

opening for a button. A button shall be located below the bottom welt corresponding in location with the tab, which shall be interlined with non-woven for added durability. There shall be a dart centered above each hip pocket to waistband. Dart shall be approximately 2-3/4" long tapered from 3/8" at waistband and shall be installed with automatic equipment for a clean non-puckered finish.

Creases:

The leg creases, front and back will have a silicone bead put in by using the Lintrak process.

Stitching, Pressing & Finishing:

Trouser must be stitched with matching thread. Trouser must be neatly pressed on Hothead Presses and properly shaped. Out seams and inseams are edge serged on automatic equipment for uniformity of quality and shall be pressed open for a smooth pucker-free finish with repeated cleaning and pressing. Trouser must be cleaned and finished to eliminate loose threads.

Stripe:

Trousers shall have a 3/4" stripe of the 100% polyester material in brown (7451-7062) Milekin. Stripe is to be sewn from the bottom of the waistband to the bottom of the trouser leg and is to be sewn into the trouser side seam.

Labels:

Trouser must have a permanent label providing care instructions and small woven label indicating waist size. A removable paper ticket showing the size, fabric content, cut number, and WPL or RN number must be on the outside of the waistband. Ticket to be matchbook style installed with plastic staples for easy removal without damaging trouser material and showing size when trousers are stacked.

Origin:

Make in USA

Warranty:

One year against workmanship or fabric defects.

Color:

1. **Taupe with 3/4" brown stripe** sewn on seam from waistband to bottom. (Brown 3/4" Stripe to be sewn into seam of pants - not sewn on top of seam)

(A) Supervisors - 1/2" **gold** (not yellow) stripe sewn on top of the 3/4" brown.

Sample of stripes will be supplied with Bid Response.

2. **Brown**

Item 7. TIES

Material:

55% poly/45% wool

Color:

Taupe

Style:

Four in hand or clip on

Item 8. SERVING SINCE/NAMEPLATES

Blackinton #J4, Hi-Glo, 2" x 3/8" Name Plate, Clutchback

Blackinton #J6, Hi-Glo, 2" x 3/4" Serving Since, Clutchback

Item 9. EMBLEMS

Sheriff Office & Corrections

A. Type currently used by department (sample will be provided upon request)

Item 10. OUTER BASKET WEAVE GUN BELT

Safariland #94, High Gloss Finish in Black Buckleless Belt with Velcro fastening on inner sides, Outer Duty Belt

Item 11. INNER BASKET WEAVE GUN BELT

Safariland #99, High Gloss Finish in Black Buckleless Belt with Velcro fastening Inner Trouser Belt

Item 12. RANK INSIGNIA

Blackinton A1975 Gold Collar Brass- Captain
Blackinton A1973 Gold Collar Brass- Lieutenant
Blackinton A8765A Gold Collar Brass-Corporal
Blackinton A8765 Gold Collar Brass -Sergeant
Blackinton A982-3 Gold Oak Leaf
Blackinton A2015 Gold Eagles
Blackinton A5697 Gold 3/4" Star
Blackinton A3941 Gold 5/16" CHIEF
Blackinton Style #15 Custom Insignia 3/8" Gold "BCSO"

Item 13. SHERIFF STRAW HAT

Stratton S-40 Campaign Style Brown (no holes)

Item 14. HAT STRAPS

Stratton ST-3P-BK, 3-piece hat straps for straw hat

Item 15. GOLD CORDS WITH ACORNS

Stratton CD-GD, Gold hat cords with acorns for straw hat

Item 16. TROOPER HAT RAINCOVER

Premier -9000 Series (To fit Campaign Style)

Item 17. Cap - Flexfil Mid-Profile Cap

Flexfit Mid-Profile Cap Z5001

Construction: 6 panel, mid-profile, fitted cap with buckram. Spandex sweat band retain to retain shape, 8 rows of stitching on Permacurv visor, silver under visor. Taped seams. To fitting a wide variety of head sizes.

Crown Height: 3 1/2" (From bottom of cap to top of cap)

Bill Length: 2 1/2" (from point bill attaches to cap to end)

Hat Band: 6 3/4" - 7 1/4", 7 1/8"-7 5/8" (circumference of hat opening)

Blend: 98% Cotton, 2% Spandex

Sizes: S/M, L/XL

Color: Black

Item 18: SHOES

Style: G8732

Women's Oxford Work Shoes

Oxford soft-toe, easy care leather upper and a slip-resistant rubber lug outsole. Moisture-wicking nylon mesh lining with a removable EVA cushion insert and sponge rubber heel wedge.

Item 19: SHOES

Men's Bates Lite Glossy Style #942

Item 20: Women's Bates High Gloss DuraShocks Oxford Shoes

Item # 742 Bates High-Gloss DuraShocks Oxford High-Gloss

Color: High-Gloss Black

Breathable lining, cushioned removable insert, Bates DuraShocks absorbing comfort, Slip Resistant, Durable direct attach construction.

Item 21: Rocky TMC Duty Shoes 5001

Aegis Microbe Shield Applied to ROCKY Airport Footbed

Full-Grain Water-Resistant Polishable Leather

Made in the USA

Non-Metallic Stabilizer

Slip and Oil Resistant TMC Direct Attach TPU/PU outsole for Stability and Flexibility

Item 22: MEN'S PROPPER RIPSTOP BATTLE DRESS (BDU) TROUSER (NO SUBSTITUTES ALLOWED) Style: Proper F5250 (samples MUST be supplied with your Bid Response)

(F5250-25) 60% cotton/40% polyester ripstop

Weight: 6.50-7.00 oz Sq/yd

Construction: 102x48

Yarn Size: 20x13

Tear: 7x7

Tensile: 190x110

Crocking Dry: 4.0

Crocking Wet: 3.0

Colorfastness to Light: 4/20 AATCC16

Shrinkage: 3-4%

DESIGN

- Zipper fly with sturdy snap closure
- Felled inseams, outseams and seat seams
- Fused pocket flaps for clean, professional look
- Adjustable waist tabs for secure fit
- Reinforced seat and knee LABEL

The pants will have a Label attached to the bottom of the inside seat with following information: Size, Fabric Content, Care Instructions and Country of Origin.

SIZES

XS – 3XL Regular

S – XL Long

COLOR

Black 001, subdued urban digital 060, urban 063, khaki 250, 6-color desert 271, woodland 320, olive 330, tiger stripe 335, Asian tiger stripe 336, woodland digital 395, LAPD navy 450, desert digital 930.

Item 23: MEN'S PROPPER RIPSTOP LIGHTWEIGHT LONG SLEEVE TACTICAL DRESS SHIRT UNIFORM (BDU) Style Proper: F5302-38 (NO SUBSTITUTES ALLOWED) (samples MUST be supplied with your Bid Response)

FABRIC

Fabric to be 65% Poly / 35% Cotton Ripstop. Fabric must meet the following specifications to assure consistency of color, quality and wear:

Weight: 6.25-6.50 oz Sq/yd

Construction: 102x48

Yarn Size: 20X13

Tear: 7X7

Crocking Dry: 4.0

Crocking Wet: 3.0

Colorfastness to Light: 4/20 AATCC16

Shrinkage: 3-4%

Tensile: 190X110

DESIGN

The Propper Tactical Dress Shirt has a banded collar with sewn in collar stays and a dress shirt placket. The front of the shirt has two chest patch pockets with flap closure and button-down shoulder Epaulets reinforced with Box (X) Stitching.

The two front patch pockets are designed with decorative pleats and mitered corners. The button closure is centered on each flap. The left pocket will have an internal pencil pocket measuring 1 1/8-inch wide. The pocket will include a double grommet Badge Tab to be attached where needed.

The front of the shirt will have a six-button dress placket closure. All buttons will be securely sewn and properly aligned with buttons on pocket flap, 3 1/2 inches apart. The buttonholes will be straight-cut with a finished length of 1/2 to 9/16 inch.

The collar and collarstand of shirt are designed with a heavy weight interfacing to ensure a professional, crisp appearance. The collarstand will be closed with a horizontal centered button and buttonhole to be in line with vertical buttonholes on front placket without distorting the left or right front.

The sleeves will be finished with a 1-inch double turned hem.

The collar, collarstand, epaulets, pocket flaps and placket will have fused lining made of heavy weight poly core interlining. For added comfort and durability the back of the shirt will have a self-material double yoke and all interior seams will be safety stitched. The collar, pocket flaps and cuffs will be stitched 1/4 inch around all edges. The extra-long dress shirttail bottom will be finished with a double turned 1/4 inch hem.

LABEL

The shirt will have a Label attached to the bottom of the collarstand with the following information: Size, Fabric Content, Care Instructions and Country of Origin.

SIZES

Regular, S-XL, Long S-3XL

COLOR

Black, Dark Navy, Sheriffs Brown, Khaki, Olive, Dark Grey, Grey and LAPD Navy

Item 24: PROPPER LEIGHTWEIGHT SHORT SLEEVE RIPSTOP TACTICAL DRESS SHIRT WITH CROSS TACKED SHOULDER EPAULETS F5301-38 (NO SUBSTITUTES ALLOWED)
(samples MUST be supplied with your Bid Response)

FABRIC

Fabric to be 65% Poly / 35% Cotton Ripstop. Fabric must meet the following specifications to assure consistency of color, quality and wear:

Weight: 6.25-6.50 oz Sq/yd

Construction: 102x48

Yarn Size: 20X13

Tear: 7X7

Tensile: 190X110

Crocking Dry: 4.0

Crocking Wet: 3.0

Colorfastness to Light: 4/20 AATCC16

Shrinkage: 3-4%

DESIGN

The Propper Tactical Dress Shirt has a banded collar with sewn in collar stays and a dress shirt placket. The front of the shirt has two chest patch pockets with flap closure and button-down shoulder Epaulets reinforced with Box (X) Stitching.

The two front patch pockets are designed with decorative pleats and mitered corners. The button closure is centered on each flap. The left pocket will have an internal pencil pocket measuring 1 1/8-inch wide. The pocket will include a double grommet Badge Tab to be attached where needed.

The front of the shirt will have a six-button dress placket closure. All buttons will be securely sewn and properly aligned with buttons on pocket flap, 3 1/2 inches apart. The buttonholes will be straight-cut with a finished length of 1/2 to 9/16 inch.

The collar and collarstand of shirt are designed with a heavy weight interfacing to ensure a professional, crisp appearance. The collarstand will be closed with a horizontal centered button and buttonhole to be in line with vertical buttonholes on front placket without distorting the left or right front.

The sleeves will be finished with a 1-inch double turned hem.

The collar, collarstand, epaulets, pocket flaps and placket will have fused lining made of heavy weight poly core interlining. For added comfort and durability the back of the shirt will have a self-material double yoke and all interior seams will be safety stitched. The collar, pocket flaps and cuffs will be stitched 1/4 inch around all edges. The extra-long dress shirttail bottom will be finished with a double turned 1/4 inch hem.

LABEL

The shirt will have a Label attached to the bottom of the collarstand with the following information: Size, Fabric Content, Care Instructions and Country of Origin.

SIZES

XS-4XL

COLOR

Black, Dark Navy, Sheriffs Brown, Khaki, Olive, Dark Grey, Grey and LAPD Navy

Item 25: RIPSTOP BOONIE HAT

Propper Cotton Ripstop Boonie Hat #F550155001 – OD Green – 100% Cotton ripstop material, 2.5 inch brim, 3/4 inch nylon webbing and Nylon adjustable chin cord. **Must Provide All Sizes and Sample in Bid Response Sheet**

Item 26: RIPSTOP TDU SHIRT

5.11 Tactical Taclite TDU Shirt #72054 OD Green & Khaki – Long Sleeve and Short Sleeve with and without 5.11 Tactical Chroma Flex Template Badges #81030 – 5 Point Star in Gold. **Must Provide All Sizes and Sample in Bid Response Sheet**

Item 27: RIPSTOP TDU PANTS

5.11 Tactical Ripstop TDU Pants #74003 OD-Green & Khaki - Hidden zipper (mock button up) **Must Provide All Sizes and Sample in Bid Response Sheet** Must come in women's sizes also.

Item 28: BELT

Bianchi Accumold Outer Belt, Black, Model #7200

Item 29: BELT

Bianchi Model #7950 - AccuMold Elite Duty Nylon (2.25" width) Black

Item 30: BELT LINER

Bianchi Model #7205 Nylon Liner Belt Black

Item 31: GLOVES

Kevlar lined frisk gloves Style #RFK-300

Item 32: JACKET

Port Authority Competitor Jacket JP54; color is **black on black**, Teklon nylon shell: Fleece lining, elastic waistband, elastic cuffs with adjustable straps, nylon-lined sleeves, lower slash pockets with zip closures, Interior pocket with zip closure, Port Pocket

Item 33: H20 PROOF ALL SEASON RAIN PARKA

Tru-Spec Style # 2492; Black in color;

ITEM 34: POLAR FLEECE JACKET

Tru-Spec Style # 2434; Black in color

Item 35: 5.11 Tactical Packable Police Jacket - (raid) (w/optional SHERIFF on back)

Mic loops, a vertical chest pocket and hand pockets. Made of durable nylon with YKK zippers and Prym Snaps.

Features: Wind resistant Hidden chest pocket Mic Loops Lightweight Packable.

ITEM 36. RECESSED BADGE HOLDER WITH BELT CLIP

Perfect fit Item # BD023 customized to 5 star or 7 star badges

Item 37: RECESSED BADGE HOLDER WALLET

Smith & Warren Style # BC100-D4. Dress Leather Bifold Wallet w/Single ID; Max Badge Size: 2.75" x 3.75"

Item 38: MAGAZINE HOLDER

Safariland 77-83-4HS double-black basketweave, unlined, for 2 1/4" Belt loop.

Item 39: HANDCUFF HOLDER

Safariland #90-4HS, hinged cuff case, black, basketweave

Item 40: FLASHLIGHT HOLDER

Safariland 306, open top Stinger flashlight holder, black basketweave

Item 41: HOLSTER (Right Hand) – Glock .22

Safariland 6360 ALS Level III w/Hi-Ride UBL 6360-832-481 Glock 4.5" BBL: 17,22 w/ITI M3, TLR – 1, Surefire, X200, LAS-Tac 2 SSL-1 Belt Loop: 2.25" Black basketweave, lined right hand.

Item 42: HOLSTER (Left Hand) – Glock .22

Safariland 6360 ALS Level III w/Hi-Ride UBL 6360-832-482 Glock 4.5" BBL: 17,22 w/ITI M3, TLR – 1, Surefire, X200, LAS-Tac 2 SSL-1 Belt Loop: 2.25" Black basketweave, lined left hand.

Item 43: HOLSTER (Right Hand) – Glock .23

Safariland 6360 ALS Level III w/Ride UBL Holster – STX Basket Weave Right Hand 6360-2832-481, lined right hand, belt loop 2.25"

Item 44: HOLSTER (Left Hand) – Glock .23

Safariland 6360 ALS Level III w/Ride UBL Holster – STX Basket Weave Left Hand 6360-2832-482, lined left hand, belt loop 2.25"

Item 45: BELT KEEPERS

Bianchi 6406 for nylon belts

Item 46: BELT KEEPERS

Safariland 62-4HS for basketweave leather belt

Item 47: BATON

ASP 26", F26B

Item 48: 5.11 Tactical Polo Shirts – Style #71049 (samples for Polo Shirt MUST be supplied with your Bid Response)

Material:

5.11 Tactical Performance Polo Men's Shirt in Black, Hunter Green, Tan, Red, White

No Shrinking, wrinkling or fading

No Collar Curl

Shirt must come with and without 5.11 Tactical ChromaFlex Template Badge #81030 5 Point Star Gold

Item 49: 5.11 Tactical Polo Shirts – Style #61165 (samples for Polo Shirt MUST be supplied with your Bid Response)

Material:

5.11 Tactical Performance Polo Women's Shirt in Black, Hunter Green, Tan, Red, White

No Shrinking, wrinkling or fading

No Collar Curl

Shirt must come with and without 5.11 Tactical ChromaFlex Template Badge #81030 5 Point Star Gold

Item 50: 5.11 Tactical Leather Casual Belt

5.11 Leather Casual Belts are made for everyday-casual, plainclothes or undercover wear.

Full grain leather with Permastiff™ insert to support weapon

1-1/2" wide

Buckle features "I-Beam" construction for rugged durability

Black with nickel buckle or Brown with brass buckle

Hidden key keeper on inside of belt

Item 51: Under Armour Tactical Stealth Beanie

100% acrylic in a classic cuffed style that is lined with Under Armour® moisture-wicking liner

Item 52: BDU Pocket Trouser

Color: Multi Cam

6.5 oz. 65% polyester / 35% cotton fiber blend rip-stop material. Machine washable and dry cleanable cotton blend provides user comfort, uniform appearance, durability, and easy care.

Interlining: 100% polyester

BDU (swat) trouser

Tailored split-seam construction

Dress Uniform Style

Two front quarter pockets

Two pleated BDU style cargo side pockets

Two hip pickets with flaps

Snap front closure

Stretch waistband with side spot elastic

Belt loops inserted at the bottom of waistband and tacked to the top

Reinforced knees with inside patches of pocketing fabric

Knee patches shall accept optional removable knee pads

The patterning shall be loose fitting through the seat and thighs to allow unrestrained movement

Item 53: Short Sleeve Street Shirt – Must provide Sample with your Bid Response

Style #8972

Color: Brown

Garments must be manufactured to ISO 9001 quality assurance standard.

Shell Fabric: 10 oz. 80% polyester 20% rayon plain weave. Machine washable and dry cleanable, wool blend provides user comfort, uniform appearance, durability and easy care.
100% Polyester Waffle Knit and easy-care wicking and antimicrobial finish

Trim: Mesh Lining: 100% Polyester mesh; Interlining: Small Parts-100% Polyester, Front Placket: 50% Polyester 50% Cotton; Buttons – Melamine, 20 ligne, matching shell fabric;
Crosswalk Reflective Trim; ½” wide

Design and Construction: Short sleeve pullover shirt with woven fabric sleeves and woven/knit fabric body. Set in shoulder design, 3-button center front placket with convertible collar, Yoke lined with breathable mesh fabric, on demand reflective crosswalk Scotchlite under back of collar and on the inside underarm of sleeves at hem.

Item 54: Long Sleeve Street Shirt – Must provide Sample with your Bid Response

Style# 8971

Color: Brown

Garments must be manufactured to ISO 9001 quality assurance standard.

Shell Fabric: 10 oz. 80% polyester 20% rayon plain weave. Machine washable and dry cleanable, wool blend provides user comfort, uniform appearance, durability and easy care.
100% Polyester Waffle Knit and easy-care wicking and antimicrobial finish

Trim: Mesh Lining: 100% Polyester mesh; Interlining: Small Parts-100% Polyester, Front Placket: 50% Polyester 50% Cotton; Buttons – Melamine, 20 ligne, matching shell fabric;
Crosswalk Reflective Trim; ½” wide

Design and Construction: Long sleeve pullover shirt with woven fabric sleeves and woven/knit fabric body. Set in shoulder design, 3-button center front placket with convertible collar, Yoke lined with breathable mesh fabric, 2 button adjustable cuffs, on demand reflective crosswalk Scotchlite under back of collar and on the inside underarm of sleeves at hem.

Item 55: Armorskin Vest w/Optional Body Worn – Must provide samples with your Bid Response

Style #8970

Color: Sheriff Brown

Garments must be manufactured to ISO 9001 quality assurance standard.

Shell Fabric: 10 oz. 80% polyester 20% rayon plain weave. Machine washable and dry cleanable, uniform appearance, durability and easy care.
Breathable, 4-way stretch, 5.5 oz Nylon with Lycra mesh technical knit with high abrasion, pill resistance and anti-microbial finish.

Trim: Mesh Lining: 100% Polyester mesh; Interlining: Small Parts-100% Polyester, Front Placket: 50% Polyester 50% Cotton; Buttons – Melamine, 20 ligne, matching shell fabric;
Body Binding- Self Fabric, Shoulder Binding – 100% Lycra, Hem Binding – 100% Nylon, Hem Facing – 100% Nylon Ripstop with honeycomb printed back, Grosgrain Ribbon – 1” wide.

BODY CAMERA ATTACHMENT:

Customized access to holster and phone/camera uses YKK brand #3 reverse tape coil zipper in 9” length. Camera access is from wearer’s right-side front of placket, under top placket, to attachment location on wearers left side for men & women. Placement of camera holster and patch is specific for optimal performance of equipment and stability of application. Main eye-hole is created by using a Stimpston non-rusting metal #5.5 @ 11/16” rolled rim grommet and washer. Velcro USA hook and loop patch with two width measurements; one for in-production addition or second for post-production customization

add-in; ref: COM-BW-1022 & COM-BW-1023. Patch uses Tandy size# 16 Ligne non-rusting snaps with specific spacing to accommodate lightweight polymer holster facilitating removal and insertion for user.

Design and Construction: Armorskin vest with shaped stretch side panels, two-way zippered single welt side openings, 5 military style creases stitched on front and back, Mitered pleated pockets with scalloped flaps, pencil opening on left and right pocket flap, hook and loop closure, Two (2) Napoleon style pocket openings beneath the upper pleated pockets, Fully lined with breathable mesh fabric, Inside shoulder opening for attachment of carrier hook and look shoulder strap, Epaulets, On demand Scotchlite reflective on top edge of front pockets, Badge eyelets with internal support strap, Grosgrain ribbon loops sewn to inside for suspender application.

Customization (Optional) Name Tab, Metal Buttons on fronts, epaulets, and pocket flaps and ArmorSkin suspenders.

Standard Size Range – Unisex: 2XS, XS, XS/S, S, S/M, M, M/L, L, L/XL, XL-6XL

Measurements: Size Large Regular:

½ Chest – 23.5; Back Length – 18.625; Front Length – 16.25

Item 56: Armorskin Suspension System

Style: #174

Color: Black

Balances weight of the duty belt between the shoulders and hips and allows for a looser duty belt fit.

Durable nylon webbing material with adjustable padding for shoulder comfort.

Quick release hardware to attach to current keepers to allow for easy removal of trousers and duty belt.

Item 57: Ripstop BDU Armor Skin™ Must provide samples with your Bid Response

Style: #8470

Color: Silver Tan

Garments must be manufactured to ISO 9001 quality assurance standard.

Shell Fabric:

65% Polyester 45% Cotton Ripstop. Machine washable and dry cleanable fabric provides user comfort, uniform appearance, durability, and easy care.

Breathable, 4-way stretch, 5.5 oz. Nylon with Lycra mesh technical knit with high abrasion, pill resistance and anti-microbial finish.

Trim:

Mesh Lining: 100% Polyester Mesh

Interlining: Body: 100% polyester, Front Placket: 50% polyester 50% Cotton.

Body Binding: Self Fabric

Should Binding: 100% Lycra

Hem Binding: 100% Nylon

Hem Facing: 100% Nylon Ripstop with honeycomb printed back

Grosgrain Ribbon: 1" wide

Design and Construction:

Armorskin vest with shaped stretch side panels

Two-way zippered single welt side openings

(2) Upper BDU style patch pockets with asymmetrical flaps

(2) Napoleon style pocket openings beneath the upper patch pockets

Fully lined with breathable mesh fabric

Inside shoulder openings for attachment of carrier hook and look shoulder strap

Mic tab on front placket, between first and second button

Epaulets

Badge eyelets with internal support strap

Grosgrain ribbon loops sewn to inside for suspender application

Measurements:

Unisex: Size Large, Regular

½ Chest: 23.5

Back Length 18.625

Front Length 16.875

Item 58: Long Sleeve Ripstop Armorskin™ Base Shirt Must provide samples with your Bid Response.

Style: 8471

Color: Silver Tan

Garments must be manufactured to ISO 9001 quality assurance standard.

Shell Fabric:

65% Polyester 45% Cotton Ripstop. Machine washable and dry cleanable fabric provides user comfort, uniform appearance, easy care wicking finish.

100% Polyester Waffle Knit. Machine washable and dry cleanable fabric provides user comfort, uniform appearance, durability, and easy-care wicking and antimicrobial finish

Trim:

Lining: 100% Polyester Satin

Mesh Lining: 100% Polyester Mesh

Interlining; Small Parts: 100% Polyester, Front Placket: 50% Polyester 50% Cotton

Buttons: melamine, 20 ligne, matching shell fabric

Velcro: 1" black hook and loop

Design and Construction

Long sleeve pullover shirt with woven fabric sleeves and woven/knit fabric body

Set in shoulder design

3-button center front placket with convertible collar

Yoke lined with breathable mesh fabric

Sleeve cuffs with Velcro closure

Standard Size Range

Men's Sizes – S-M-L, (30-31), (32-33), (34-35), (36-37)

Measurements:

Men's: size Large, regular

Neck: 18.5

½ Chest: 23

Back Length: 32.5

Item 59: Short Sleeve Ripstop Armorskin™ Base Shirt Must provide samples with your Bid Response.

Style: 8472

Color: Silver Tan

Garments must be manufactured to ISO 9001 quality assurance standard.

Shell Fabric:

65% Polyester 45% Cotton Ripstop. Machine washable and dry cleanable fabric provides user comfort, uniform appearance, easy care wicking finish.

100% Polyester Waffle Knit. Machine washable and dry cleanable fabric provides user comfort, uniform appearance, durability, and easy-care wicking and antimicrobial finish

Trim:

Lining: 100% Polyester Satin

Mesh Lining: 100% Polyester Mesh

Interlining; Small Parts: 100% Polyester, Front Placket: 50% Polyester 50% Cotton

Buttons: melamine, 20 ligne, matching shell fabric

Velcro: 1" black hook and loop

Design and Construction

Long sleeve pullover shirt with woven fabric sleeves and woven/knit fabric body

Set in shoulder design

3-button center front placket with convertible collar

Yoke lined with breathable mesh fabric

Sleeve cuffs with Velcro closure

Standard Size Range

Men's Sizes – S-M-L, (30-31), (32-33), (34-35), (36-37)

Measurements:

Men's: size Large, regular

Neck: 18.5

½ Chest: 23

Back Length: 32.5

Item 60: Operational Trouser Must provide samples with your Bid Response.

Style: 8835

Color: Silver Tan

Garments must be manufactured to ISO 9001 quality assurance standard.

Shell Fabric

6.7 oz. 65% polyester / 35% cotton fiber blend rip-stop material. Machine washable and dry cleanable cotton blend provides user comfort, uniform appearance, durability, an easy care.

Trim:

Interlining: 100% polyester

Design and Construction:

Operational trouser

Loose fitting through seat and thighs to allow unrestrained movement

Closed-seam construction

Dress uniform style

Two (2) front "L" shaped quarter pockets

Two (2) cargo side pockets with center pleat and concealed zipper closure

Magazine pocket inside of left cargo pocket

Cell phone pocket inside of right cargo pocket

Two overlapping single welt hip pockets

Left exterior single welt phone pocket

Side spot elasticized waistband and snap front closure

Silicone shirt grip tape inside waistband

Waistband with belt loops inserted at the bottom and tacked to the top

Articulated knee design with darts and rear seam.

Hemmed

Standard Size Range:

Men's: Regular Length: even waist sizes 28-54; odd sizes 31-37

Women's Regular Length: even dress sizes 0-24

Measurements:

Regular Length Men's: Waist size 36:

½ Waist (relaxed): 18.5; ½ Waist (stretched) 19.5

Seat: 23.5

½ Knee: 11.125

½ Bottom Leg: 9

Inseam: 37

Out seam: 46.375

Front Rise: 9.375

Back Rise: 10.5

Women's: Regular Length: Dress Size 12

½ Waist – (relaxed): 17.25; ½ Waist - (stretched): 18.25

Seat: 22.5

½ Knee: 10.562

½ bottom leg: 9.125

Inseam: 35

Out seam: 44

Front Rise: 8.875

Back Rise: 9.75

Item 61: SSH122 Short Sleeve Brown Super Shirt with optional Body Worn.

Style # 8675

FABRIC:

Content – 100% Polyester plain weave tropical weight. Machine washable and dry cleanable polyester provides user comfort, uniform appearance, durability, and easy care.

Weight – 4.1-4.6 oz. per square yard

Physical Properties:

- Warp Yarn – 1/150
- Filling Yarn – 2/150
- Picks/inch – 51
- Ends/inch – 78
- Warp Stretch – 9-13
- Filling Stretch – 3-7

SIDE KNIT FABRIC:

Content – 92% Nylon 8% Lycra mesh technical knit with high abrasion, pill resistance and anti-microbial finish. Breathable, 4-way stretch.

Weight – 6 oz. per square yard

Physical Properties:

- Pilling Resistance (Face) – 5
- Stretch (elongation) – 105 x 170
- Bursting Strength, min (psi) – 100

Colorfastness:

- Laundering shade change, min – 4
- 2A washes fastness – 4
- Dry/Wet Crocking – 4

TOP FUSING: The following small parts shall be top fused prior to sewing. Plackets, cuffs, collar, pocket flaps and epaulets.

GENERAL DESIGN:

Duty shirt constructed using fabrics with stain release technology & UV protection with side stretch panels for fit and comfort that double as ventilation in the warm weather. Night-time visibility with deployable reflective material and zippered front with mock buttons.

COLLAR:

Points medium spread are to be 3-1/4" in length and are to be topstitched 1/4" from the edge. Back of the stand measures 1-1/4". Permanent stays 2-1/2" in length and 1/4" wide, to be sewn inside collars so that no stitches are made through bottom leaf. Stand shall fasten with one (1) button. Inner stand and inner yoke to be lined with matching 100% Polyester inner lining, cut on the bias, to assure that the collar will lie properly. Collar shall be top fused. Reflective crosswalk trim heat-sealed onto back of collar.

SLEEVES:

Straight style, one piece. The cuffs to be 2-1/4" in width, and to fasten with two-four-hole buttons. The cuff shall be topstitched 1/8" at the bottom, and 1/16" from the edge of the top. An additional stitch shall run across the cuff 1/4" down from the top edge of the cuff. There shall be a sleeve vent opening 4-1/2" long from the top of the cuff. The vent placket shall be 1" wide; and shall close with a button and buttonhole, spaced approximately halfway up the opening. The sleeve seam, as well as the sleeve setting seam (i.e. securing it to be body of the shirt) must be made by a narrow safety stitch, so as to properly strengthen the seam, as well as prevent the fabric from raveling. Cuffs are to be top fused and fully lined to give body by sewing in a self-fabric inner lining, cut straight to retain its shape. Reflective crosswalk trim shall be heat-sealed on the inside edge of cuff.

FRONT:

The front shall have a center facing 1-1/2" wide, extending to the bottom of the shirt and be made of the same material as the shirt fabric with two rows of stitching 1" apart and 1/2" from the edge. This center facing shall be top fused to give body. There shall be a 14" Nylon zipper with a compatible colored tape sewn to the front of the shirt, replacing the second, third, fourth, and fifth buttons which are to be sewn on top of the buttonhole on the top center front facing. The buttonholes on the center front shall be placed 3/4" from the edge and spaced so that the distance from the center of the button to the center of the next button is 3-1/2". The neck button, first front button and bottom front button shall be functional.

MESH SIDE PANELS:

Mesh panels are sewn into side seam of sleeve and body with 1/16" topstitching around mesh panels. Sleeve mesh panels are sewn at the upper portion of the sleeve seam and measure 2-3/4" at widest part and tapers down 9" long to blend with sleeve seam. Side panels measures 2-3/4" wide top and 4-3/4" at bottom hem and sewn to the side seams of the front and back of shirt. Hem shall be clean finished using double bend back folder with 1/4" top stitching gauge. There is a 1" opening below the notebook pocket on both side seams towards the front.

POCKETS:

To have two (2) hidden napoleon pockets and two (2) breast pockets. Breast pockets to be topstitched 1/16" from the edge, with pointed corners, to finish 5-1/2" wide and 6-1/2" long. The left and right breast pockets shall have a pencil compartment 1-1/4" wide. Breast pockets to have 1-1/2" box pleat stitched top and bottom to prevent spreading. Reflective crosswalk trim heat sealed 3/8" below top edge of pocket.

FLAPS:

Has two (2) scalloped flaps, top-stitched 1/16" from the edge, to finish 5-3/4" in width, 2-3/4" in long at center, 2-1/2" in long at sides. Flaps are secured to the front of the shirt with two (2) rows of stitching 3/16" apart. Left and right flaps have a pencil opening corresponding to pencil compartment in the pocket. Flaps are fully lined to give body, by sewing in a 100% Dacron polyester interlining, 425 weight mellowpress, cut straight. There is to be a button and buttonhole sewn on the flap. The side points of the flaps are to be secured to the pocket by means of Velcro fasteners sewn onto the flaps and pockets, the hook portion being stitched to the pocket and pile portion sewn to the underside of the flap. The pile piece sewn to the flap shall not be sewn through and through the flap, but must be attached during the manufacturing process before the flap is assembled to prevent the stitching from showing.

BADGE SLING:

Is reinforced on the inside of the shirt by means of a strip of shirt material 1-1/2" wide, stitched and folded, so that there are no raw edges. This reinforcement strip is to be set approximately 2" down from the top of the pocket, to be caught in the double stitching of the flap setting stitches and extend and be caught in the joining seam at the front of yoke. To have two small horizontal buttonholes 1-3/8" apart with the button buttonhole 1-1/4" above the top of the left flap.

SHOULDER:

The shoulder strap shall be topstitched 1/16" from the edge and be pointed at the end toward the neck of the shirt. The other end shall be sewn in the sleeve and taper to 1-1/2" wide. The length is to be graduated conforming to the size of the shirt. The strap shall be cross stitched to the shoulder approximately 2" from the sleeve head seam.

BACK YOKE:

One-piece back yoke fully lined with matching Nylon Sateen or Dacron Polyester. The yoke is to measure approximately 4-1/4" high at the center back.

MIC TAB:

A single microphone attachment tab is centered vertically on the front placket, between second and third button.

THREAD:

All thread shall be polyester wrapped on monofilament polyester. Color to match.

STITCHING:

All stitching conforms to Federal Standard 751 specifications (FED-STD-751). All stitch types are sewn at stitch per inch (S.P.I.) rates individually set by operation at no less than 10 S.P.I. and not more than 12 S.P.I. to insure extended sewn wear life. All thread tension is evenly maintained to eliminate right or loose stitching. All seam allowances are to be maintained so that there are no raw edges, run offs, twist, pleats, puckers or open seams.

PERMANENT MILITARY CREASE:

Shirt has permanent 1/16" military stitched-in creases. One crease in each front, extends from hem to shoulder joining seam. Front pockets and flaps are centered over the crease. Crease is not to run through pocket of flap. Three (3) vertical creases in back; middle crease on center back line and side creases spaced equally from center crease.

BODY CAMERA ATTACHMENT:

Customized access to holster and phone/camera uses YKK brand #3 reverse tape coil zipper currently on front of shirt. Camera access is from wearer's right-side front of placket, under top placket, to attachment location on wearers left side for men & women. Placement of camera holster and patch is specific for optimal performance of equipment and stability of application. Main eye-hole is created by using a Stimpston non-rusting metal #5.5 @ 11/16" rolled rim grommet and washer. Velcro USA hook and loop patch with two width measurements; one for in-production addition or second for post-production customization add-in; ref: COM-BW-1022 & COM-BW-1023. Patch uses Tandy size# 16 Ligne non-rusting snaps with specific spacing to accommodate lightweight polymer holster facilitating removal and insertion for user

SIZES:

Permanent size marking giving neck size to be located inside of collar.

CARE LABEL:

Care instructions to be on hem of shirt in front.

PRESSING & FINISHING:

Shirt shall be carefully pressed by hand in a first-class manner. All loose threads to be thoroughly trimmed.

STANDARD SIZE RANGE:

Men's: 14.5 – 20.5, (30-31), (32-33), (34-35), (36-37), (38-39) Sleeve Lengths

Women's: 30-54, Short and Regular Lengths

MEASUREMENTS:

Men's: Size 15.5, Regular

Neck:	16.75	(plus or minus 0.25 inches)
1/2 Chest:	23	(plus or minus 0.75 inches)
Back Length:	32.5	(plus or minus 0.5 inches)

Women's: size 36, regular

Neck:	15	(plus or minus 0.5 inches)
1/2 Chest:	20.875	(plus or minus 0.75 inches)
Back Length:	28.5	(plus or minus 0.5 inches)

Item 62: SSH122 Long Sleeve Sleeve Brown Super Shirt with optional Body Worn.

Style # 8670

FABRIC:

Content – 100% Polyester plain weave tropical weight. Machine washable and dry cleanable polyester provides user comfort, uniform appearance, durability, and easy care.

Weight – 4.1-4.6 oz. per square yard

Physical Properties:

- Warp Yarn – 1/150
- Filling Yarn – 2/150
- Picks/inch – 51
- Ends/inch – 78
- Warp Stretch – 9-13
- Filling Stretch – 3-7

SIDE KNIT FABRIC:

Content – 92% Nylon 8% Lycra mesh technical knit with high abrasion, pill resistance and anti-microbial finish. Breathable, 4-way stretch.

Weight – 6 oz. per square yard

Physical Properties:

- Pilling Resistance (Face) – 5
- Stretch (elongation) – 105 x 170
- Bursting Strength, min (psi) – 100

Colorfastness:

- Laundering shade change, min – 4
- 2A washes fastness – 4
- Dry/Wet Crocking – 4

TOP FUSING: The following small parts shall be top fused prior to sewing. Plackets, cuffs, collar, pocket flaps and epaulets.

GENERAL DESIGN:

Duty shirt constructed using fabrics with stain release technology & UV protection with side stretch panels for fit and comfort that double as ventilation in the warm weather. Night-time visibility with deployable reflective material and zippered front with mock buttons.

COLLAR:

Points medium spread are to be 3-1/4" in length and are to be topstitched 1/4" from the edge. Back of the stand measures 1-1/4". Permanent stays 2-1/2" in length and 1/4" wide, to be sewn inside collars so that no stitches are made through bottom leaf. Stand shall fasten with one (1) button. Inner stand and inner

yoke to be lined with matching 100% Polyester inner lining, cut on the bias, to assure that the collar will lie properly. Collar shall be top fused. Reflective crosswalk trim heat-sealed onto back of collar.

SLEEVES:

Straight style, one piece. The cuffs to be 2-1/4" in width, and to fasten with two-four-hole buttons. The cuff shall be topstitched 1/8" at the bottom, and 1/16" from the edge of the top. An additional stitch shall run across the cuff 1/4" down from the top edge of the cuff. There shall be a sleeve vent opening 4-1/2" long from the top of the cuff. The vent placket shall be 1" wide; and shall close with a button and buttonhole, spaced approximately halfway up the opening. The sleeve seam, as well as the sleeve setting seam (i.e. securing it to the body of the shirt) must be made by a narrow safety stitch, so as to properly strengthen the seam, as well as prevent the fabric from raveling. Cuffs are to be top fused and fully lined to give body by sewing in a self-fabric inner lining, cut straight to retain its shape. Reflective crosswalk trim shall be heat-sealed on the inside edge of cuff.

FRONT:

The front shall have a center facing 1-1/2" wide, extending to the bottom of the shirt and be made of the same material as the shirt fabric with two rows of stitching 1" apart and 1/2" from the edge. This center facing shall be top fused to give body. There shall be a 14" Nylon zipper with a compatible colored tape sewn to the front of the shirt, replacing the second, third, fourth, and fifth buttons which are to be sewn on top of the buttonhole on the top center front facing. The buttonholes on the center front shall be placed 3/4" from the edge and spaced so that the distance from the center of the button to the center of the next button is 3-1/2". The neck button, first front button and bottom front button shall be functional.

MESH SIDE PANELS:

Mesh panels are sewn into side seam of sleeve and body with 1/16" topstitching around mesh panels. Sleeve mesh panels are sewn at the upper portion of the sleeve seam and measure 2-3/4" at widest part and tapers down 9" long to blend with sleeve seam. Side panels measures 2-3/4" wide top and 4-3/4" at bottom hem and sewn to the side seams of the front and back of shirt. Hem shall be clean finished using double bend back folder with 1/4" top stitching gauge. There is a 1" opening below the notebook pocket on both side seams towards the front.

POCKETS:

To have two (2) hidden napoleon pockets and two (2) breast pockets. Breast pockets to be topstitched 1/16" from the edge, with pointed corners, to finish 5-1/2" wide and 6-1/2" long. The left and right breast pockets shall have a pencil compartment 1-1/4" wide. Breast pockets to have 1-1/2" box pleat stitched top and bottom to prevent spreading. Reflective crosswalk trim heat sealed 3/8" below top edge of pocket.

FLAPS:

Has two (2) scalloped flaps, top-stitched 1/16" from the edge, to finish 5-3/4" in width, 2-3/4" in long at center, 2-1/2" in long at sides. Flaps are secured to the front of the shirt with two (2) rows of stitching 3/16" apart. Left and right flaps have a pencil opening corresponding to pencil compartment in the pocket. Flaps are fully lined to give body, by sewing in a 100% Dacron polyester interlining, 425 weight mellowpress, cut straight. There is to be a button and buttonhole sewn on the flap. The side points of the flaps are to be secured to the pocket by means of Velcro fasteners sewn onto the flaps and pockets, the hook portion being stitched to the pocket and pile portion sewn to the underside of the flap. The pile piece sewn to the flap shall not be sewn through and through the flap, but must be attached during the manufacturing process before the flap is assembled to prevent the stitching from showing.

BADGE SLING:

Is reinforced on the inside of the shirt by means of a strip of shirt material 1-1/2" wide, stitched and folded, so that there are no raw edges. This reinforcement strip is to be set approximately 2" down from the top of the pocket, to be caught in the double stitching of the flap setting stitches and extend and be caught in the joining seam at the front of yoke. To have two small horizontal buttonholes 1-3/8" apart with the button buttonhole 1-1/4" above the top of the left flap.

SHOULDER:

The shoulder strap shall be topstitched 1/16" from the edge and be pointed at the end toward the neck of the shirt. The other end shall be sewn in the sleeve and taper to 1-1/2" wide. The length is to be graduated conforming to the size of the shirt. The strap shall be cross stitched to the shoulder approximately 2" from the sleeve head seam.

BACK YOKE:

One-piece back yoke fully lined with matching Nylon Sateen or Dacron Polyester. The yoke is to measure approximately 4-1/4" high at the center back.

MIC TAB:

A single microphone attachment tab is centered vertically on the front placket, between second and third button.

THREAD:

All thread shall be polyester wrapped on monofilament polyester. Color to match.

STITCHING:

All stitching conforms to Federal Standard 751 specifications (FED-STD-751). All stitch types are sewn at stitch per inch (S.P.I.) rates individually set by operation at no less than 10 S.P.I. and not more than 12 S.P.I. to insure extended sewn wear life. All thread tension is evenly maintained to eliminate right or loose stitching. All seam allowances are to be maintained so that there are no raw edges, run offs, twist, pleats, puckers or open seams.

PERMANENT MILITARY CREASE:

Shirt has permanent 1/16" military stitched-in creases. One crease in each front, extends from hem to shoulder joining seam. Front pockets and flaps are centered over the crease. Crease is not to run through pocket of flap. Three (3) vertical creases in back; middle crease on center back line and side creases spaced equally from center crease.

BODY CAMERA ATTACHMENT:

Customized access to holster and phone/camera uses YKK brand #3 reverse tape coil zipper currently on front of shirt. Camera access is from wearer's right-side front of placket, under top placket, to attachment location on wearers left side for men & women. Placement of camera holster and patch is specific for optimal performance of equipment and stability of application. Main eye-hole is created by using a Stimpston non-rusting metal #5.5 @ 11/16" rolled rim grommet and washer. Velcro USA hook and loop patch with two width measurements; one for in-production addition or second for post-production customization add-in; ref: COM-BW-1022 & COM-BW-1023. Patch uses Tandy size# 16 Ligne non-rusting snaps with specific spacing to accommodate lightweight polymer holster facilitating removal and insertion for user

SIZES:

Permanent size marking giving neck size to be located inside of collar.

CARE LABEL:

Care instructions to be on hem of shirt in front.

PRESSING & FINISHING:

Shirt shall be carefully pressed by hand in a first-class manner. All loose threads to be thoroughly trimmed.

STANDARD SIZE RANGE:

Men's: 14.5 – 20.5, (30-31), (32-33), (34-35), (36-37), (38-39) Sleeve Lengths
Women's: 30-54, Short and Regular Lengths

MEASUREMENTS:

Men's: Size 15.5, Regular

Neck:	16.75	(plus or minus 0.25 inches)
1/2 Chest:	23	(plus or minus 0.75 inches)
Back Length:	32.5	(plus or minus 0.5 inches)

Women's: size 36, regular

Neck:	15	(plus or minus 0.5 inches)
1/2 Chest:	20.875	(plus or minus 0.75 inches)
Back Length:	28.5	(plus or minus 0.5 inches)

BID RESPONSE FORM BID #WG19-22

Provision of Uniforms

Date: _____

Out Of State _____ or _____ If yes, _____
Yes No Registration Number

Company Name: _____

Address: _____

Company Rep _____

(Rep. Name Typed or Printed)

Position: _____

Phone: _____

Fax: _____

Email: _____

Financing through another agency beside yourself _____ or ____xx____
Yes No

If yes, you must attach a copy of the financing agreement and all conditions to this response form:

Financing Agency Authorized Signature

A BID GUARANTEE OF \$500.00 MUST BE INCLUDED WITH YOUR BID.

**THIS PAGE MUST ACCOMPANY THE DETAILED ITEM LISTING,
ALONG WITH THE REQUIRED CATALOGS AND SAMPLES.**

Page 2 of Bid Response Form #WG19-22

Item #	Description	Style	Cost p/each
1	Convertible Jacket	Brookwood	
2	Raincoat Reversible Hi Visibility	5.11 Style 48125 Reversible	
3	Shirt, Men L/S	Flying Cross FC- 33W7800Z	
4	Sheriff Logo Safety Vest (w/Optional Body Worn)	Oralite Zip-Front 343R-S	
	Optional Body Worn		
5	Trousers, Men	Fechheimer42283	
6	Trousers, Women	Flying Cross/ Fechheimer 47293	
7	Tie	55% Poly/45% Wool	
8	Serving Since N/Plate	Blackinton J4	
	Serving Since N/Plate	Blackinton J6	
9	Emblems Sheriff Patch	samples provided	
	Small Sheriff Patch	Samples provided	
	Deputy Patch	Samples provided	
	Correction Patch	Samples provided	
	Court Security Patch	samples provided	
10	Outer Weave Gun Belt #94	Safariland #94	
11	Inner Basket Weave Gun Belt #99	Safariland #99	
12	Rank Insignia Blackinton Capt.	Blackinton A1975	
	Blackinton Lieutenant	Blackinton A1973	
	Blackinton Corporal	Blackinton A8765A	
	Blackinton Sergeant	BlackintonA8765	
	Blackinton A982-3 Gold Oak Leaf	Blackinton A982-3	
	Blackinton A2015 Gold Eagles	Blackinton A2015	
	Blackinton A5697 Gold 3/4" Star	Blackinton A5697	
	Blackinton A3941 Gold 5/16" CHIEF	Blackinton A3941	
	Blackinton CB020 Custom Insignia 3/8" Gold "BCSO"	Blackinton #15	
13	Sheriff Straw Hat (Campaign Style)	Stratton S-40	
14	Hat Straps	Stratton ST-3P-BK	
15	Gold Cords w/Acorns	Stratton CD-GD	
16	Trooper Hat Raincover	Premier - 9000 Series	
17	Cap- Flexfil Mid-Profile Cap	Flexfit Mid-Profile Cap Z5001	
18	Shoes Women's Oxfords	Style G8732	
19	Shoes Bates #942	Bates 942	
20	Women's Bates High Gloss Durashock oxford	Item#742	
21	Rocky TMC Duty Shoes 5001	Rocky 5001 TMC Duty	
22	Men's Proper RIPSTOP Battle Dress (BDU) Trouser	Propper F5250	

23	Men's Proper Ripstop Lightweight Long Sleeve Tactical Dress Shirt Uniform (BDU)	Proper F5302-38	
24	Men's Proper Ripstop Lightweight Short Sleeve Tactical Dress Uniform (BDU)	Propper F5301-38	
25	Ripstop Boonie Hat Proper	Propper# 550155001	
26	Ripstop TDU Shirt – Long Sleeve – OD Green & Khaki	5.11 Tactical #72054	
	Ripstop TDU Shirt – Long Sleeve – OD Green Khaki with 5.11 Tactical Chroma Flex Template Badges 5 Point Star	5.11 Tactical Chroma Flex #81030	
	Ripstop TDU Shirt – Short Sleeve – OD Green & Khaki	5.11 Tactical #81030	
	Ripstop TDU Shirt – Short Sleeve – OD Green & Khaki with 5.11 Tactical Chroma Flex Template Badges 5 Point Star	5.11 Tactical Chroma Flex #81030	
27	Ripstop TDU Pants – OD Green, Khaki	5.11 Tactical 74003	
28	Belt	Bianchi 7200	
29	Belt Model #7950	Bianchi 7950	
30	Belt Liner Model #7205	Bianchi 7205	
31	Gloves	RFK-300	
32	Jacket w/fleece lining	Port Authority-JP54	
33	H2O Proof All Season Rain Parka- Black	Tru-Spec #2492	
34	Polar Fleece Jacket- Black	Tru-Spec #2434	
35	5.11 Tactical Packable Police Jacket (raid)		
	(Optional SHERIFF on the back)		
36	Recessed Badge Holder with belt clip	Perfect Fit #BD023	
37	Recessed Badge Holder Wallet	Smith and Warren B100	
38	Magazine Holder	Safariland #77-83-4HS	
39	Handcuff Holder	Safariland #90-4HS	
40	Flashlight Holder	Safariland #306	
41	Holster (Right Hand) Glock .22	Safariland #6360-832-481 ALS Level III	
42	Holster (Left Hand) Glock .22	Safariland #6360-832-482 ALS Level III	
43	Holster (Right Hand) Glock .23	Safariland #6360-2832-481	
44	Holster (Left Hand) Glock .23	Safariland #6360-2832-482	
45	Belt Keepers #6406	Bianchi 6406	
46	Belt Keepers #62-4HS	Safariland 62-4HS	
47	Baton (ASP)	ASP 26" F26B	
48	5.11 Tactical Polo Shirts – Blk, Hun Grn, Tan, Red, Whi	5.11 Tactical Style #71049	
	5.11 Tactical ChromaFlex Template Badge	#81030	
49	5.11 Tactical Polo Shirts – Women's Blk,Hun Grn, Tan, Red, White	5.11 Tactical Style#61165	
	5.11 Tactical ChromaFlex Template Badge	#81030	
	5.11 Tactical ChromaFlex Template Badge	#81030	

50	5.11 Tactical Leather Casual Belt	5.11 Leather Casual	
51	Under Armor Tactical Stealth Beanie	Under Armor Beanie	
52	BDU Pocket Trouser – Multi Cam		
53	Short Sleeve Street Shirt - Brown	Style# 8972	
54	Long Sleeve Street Shirt – Brown	Style# 8971	
55	Armorskin Vest – Sheriff Brown (w/Optional Body Worn)	Style# 8970	
	Optional Body Worn		
56	Armorskin Suspension System – Black	Style# 174	
57	Ripstop BDU Armorskin – Color: Silver Tan	Style# 8470	
58	Long Sleeve Ripstop Armorskin Base Shirt – Color: Silver Tan	Style# 8471	
59	Short Sleeve Ripstop Armorskin Base Shirt - Color: Silver Tan	Style# 8472	
60	Operational Trouser – Color: Silver Tan	Style# 8835	
61	SSH122 Short Sleeve Brown Super Shirt (w/Optional Body Worn)	Style # 8675	
	Optional Body Worn		
62	SSH1221 Long Sleeve Brown Super Shirt (w/Optional Body Worn)	Style# 8670	
	Optional Body Worn		